

cm_salesforce_sources

Table	cm_salesforce_sources
Description	Salesforce Organizational Identity Sources
Plugin	Salesforce Source

Column	Format	Description	Definition	Comments
id	integer, primary key	Row identifier	autoincrement	
org_identity_source_id	integer, foreign key	Organizational Identity Source ID	cm_org_identity_sources:id	
server_id	integer, foreign key	Server ID	cm_servers:id	Added v3.2.0
serverurl	varchar(256)	Salesforce instance (may be production or sandbox)		eg: https://cs123.salesforce.com Removed v3.2.0
clientid	varchar(120)	Client ID, for registered (connected) app		Removed v3.2.0
client_secret	varchar(80)	Client secret, for registered (connected) app		This column should be encrypted Removed v3.2.0
search_contacts	boolean	Whether to query Salesforce Contact objects	<ul style="list-style-type: none">• true: Query Contacts• false: Do not query Contacts	Unintuitively, if neither search_contacts nor search_users is true, then all objects will be searched
search_users	boolean	Whether to query Salesforce User objects	<ul style="list-style-type: none">• true: Query Users• false: Do not query Users	
custom_objects	varchar(256)	Comma separated list of objects to query for additional attributes		
refresh_token	varchar(160)	Current refresh token	Salesforce OAuth	Removed v3.2.0
access_token	varchar(160)	Current access token	Salesforce OAuth	Removed v3.2.0
instance_url	varchar(256)	Current Salesforce instance	Salesforce OAuth	
groupable_attrs	blob	Cached list of attributes available for CO Group mapping		Internal format based on response from Salesforce API