

cm_unix_clusters

Table	cm_unix_clusters
Description	Unix Clusters
Plugin	Unix Cluster

Column	Format	Description	Definition	Comments
id	integer, primary key	Row identifier	autoincrement	
cluster_id	integer, foreign key	Cluster ID	cm_clusters :id	
sync_mode	varchar(2)	How to handle CO Person record updates	- F: Full Sync - M: Manual	
username_type	varchar (32)	Identifier type used to generate the Unix Account username	cm_co_extended_types :name where attribute is <i>Identifier.type</i>	For Identifiers attached to CO Person
uid_type	varchar (32)	Identifier type used to generate the Unix Account uid	cm_co_extended_types :name where attribute is <i>Identifier.type</i>	For Identifiers attached to CO Person
default_shell	varchar (64)	Default Unix shell	POSIX	
homedir_prefix	varchar (64)	String prepended to Unix Account username to construct user's home directory		
homedir_subdivisions	integer	Number of subdivisions to insert between <i>homedir_prefix</i> and username		For example, a value of 2 will (with a <i>homedir_prefix</i> of /home and a username of jsmith) result in a home directory of /home/j/s/jsmith
groupname_type	varchar (32)	Identifier type used to generate the Unix Group name	cm_co_extended_types :name where attribute is <i>Identifier.type</i>	For Identifiers attached to CO Group
gid_type	varchar (32)	Identifier type used to generate the Unix Group gid	cm_co_extended_types :name where attribute is <i>Identifier.type</i>	For Identifiers attached to CO Group
default_co_group_id	integer, foreign key	Default Group for new Unix Accounts, if configured	cm_co_groups :id	