

cm_unix_cluster_accounts

Table	cm_unix_cluster_accounts
Description	Unix Cluster Accounts
Plugin	Unix Cluster

Column	Format	Description	Definition	Comments
id	integer, primary key	Row identifier	autoincrement	
unix_cluster_id	integer, foreign key	Unix Cluster ID	cm_unix_clusters :id	
co_person_id	integer, foreign key	CO Person ID	cm_co_people :id	
sync_mode	varchar(2)	How to handle CO Person record updates	- F: Full Sync - M: Manual	Initially populated by cm_unix_clusters :sync_mode, but does not automatically follow changes to that value
status	varchar(2)	Status	- A: Active - D: Deleted - D2: Duplicate - XP: Expired - GP: GracePeriod - PA: PendingApproval - S: Suspended	
username	varchar (256)	Unix Account username	POSIX	
uid	integer	Unix Account uid	POSIX	
gecos	varchar(80)	Unix Account GECOS field		
login_shell	varchar(64)	Unix Account shell	POSIX	
home_directory	varchar(64)	Unix Account home directory		
primary_co_group_id	integer, foreign key	Primary Group for Unix Account	cm_co_groups :id	
valid_from	datetime	Unix Account is valid from this time	If null, valid any time through valid_through	
valid_through	datetime	Unix Account is valid through (but not past) this time	If null, valid any time from valid_from	