

OrgIdentity API

Add

Add a new Organizational Identity. A person must have an OrgIdentity before they can be added to a CO.

Request Format

Method	POST
URL	/org_identities.<format>
Request Body	OrgIdentity Request

Response Format

HTTP Status	Response Body	Description
201 Added	NewObjectResponse with objectType of <i>OrgIdentity</i>	OrgIdentity created
400 Bad Request		OrgIdentity Request not provided in POST body
400 Invalid Fields	ErrorResponse with details in InvalidFields element	An error in one or more provided fields
401 Unauthorized		Authentication required
403 CO Does Not Exist		The specified CO does not exist
500 Other Error		Unknown error

Delete

Remove an Organizational Identity. The person must be removed from any COs (CoPerson) before the OrgIdentity record can be removed. This method will also delete related data, such as [Addresses](#), [EmailAddresses](#), and [TelephoneNumbers](#).

Request Format

Method	DELETE
URL	/org_identities/<id>.<format>
Request Body	

Response Format

HTTP Status	Response Body	Description
200 Deleted		OrgIdentity deleted
400 Invalid Fields		<i>id</i> not provided
401 Unauthorized		Authentication required
403 CoPerson Exists	ErrorResponse with details in Memberships element. The CO ID will be in the Id attribute, and the CO Name in the Name element.	<i>id</i> must not be attached to any CoPerson. (Delete the CoPerson first.)
404 OrgIdentity Unknown		<i>id</i> not found
500 Other Error		Unknown error

Edit

Edit an existing Organizational Identity.

Request Format

Method	PUT
URL	/org_identities/<id>.<format>
Request Body	OrgIdentity Request

Response Format

HTTP Status	Response Body	Description
200 OK		OrgIdentity updated
400 Bad Request		OrgIdentity Request not provided in POST body
400 Invalid Fields	ErrorResponse with details in InvalidFields element	An error in one or more provided fields
401 Unauthorized		Authentication required
403 CO Does Not Exist		The specified CO does not exist
404 OrgIdentity Unknown		<i>id</i> not found
500 Other Error		Unknown error

View (all)

Retrieve all existing Organizational Identities.

Request Format

Method	GET
URL	/org_identities.<format>
Request Body	

Response Format

HTTP Status	Response Body	Description
200 OK	OrgIdentity Response	OrgIdentity returned
401 Unauthorized		Authentication required
500 Other Error		Unknown error

View (per CO)

Retrieve all existing Organizational Identities for the specified CO.

Request Format

Method	GET
URL	/org_identities.<format>?coid=<id>
Request Body	

Response Format

HTTP Status	Response Body	Description
-------------	---------------	-------------

200 OK	OrgIdentity Response	OrgIdentity returned
401 Unauthorized		Authentication required
404 CO Unknown		<i>id</i> not found
500 Other Error		Unknown error

View (per Identifier)

Retrieve all existing Organizational Identities attached to the specified identifier. Note the specified identifier must be attached to an Org Identity, not a CO Person.

Request Format

Method	GET
URL	/org_identities.<format>?coid=<id>&search.identifier=<identifier>
Request Body	

Response Format

HTTP Status	Response Body	Description
200 OK	OrgIdentity Response	OrgIdentity returned
401 Unauthorized		Authentication required
404 CO Unknown		<i>id</i> not found
500 Other Error		Unknown error

View (one)

Retrieve an existing Organizational Identity.

Request Format

Method	GET
URL	/org_identities/<id>.<format>
Request Body	

Response Format

HTTP Status	Response Body	Description
200 OK	OrgIdentity Response	OrgIdentity returned
401 Unauthorized		Authentication required
404 OrgIdentity Unknown		<i>id</i> not found
500 Other Error		Unknown error

Notes

- Response *format* requested is ignored where response is only via HTTP status, but must still be provided.

See Also

- [cm_org_identities](#) data model definition
- [Address API](#)
- [CoOrgIdentityLink API](#)
- [CoPerson API](#)

- [CoPersonRole API](#)
- [EmailAddress API](#) (required for [Invites](#))
- [TelephoneNumber API](#)
- [Url API](#)