## v4 Upgrade instructions from v4

Wiki	Grouper Release	Grouper	Grouper Deployment	Community	Internal Developer
Home	Announcements	Guides	Guide	Contributions	Resources

When upgrading from Grouper v4 to another v4 container, this wiki will consolidate all the steps needed to perform that upgrade.

(i) See information on Grouper Versioning here

## Note, these are in reverse order, so go from bottom to top

Date	Upgrading from version	Upgrading to Version	Note for version	Importance	Jira	Step needed if	Description
2024/03 /19	ALL	ALL	4.12.0	Not important	GRP- 5379	You run Grouper	Tomcat was upgraded, make sure any tomcat things work in UI/WS, including logs, SSL, a
2024/03 /10	ALL	ALL	4.11.0	Medium important	GRP- 5312	If you use the provisioning framework and have too much memory allocated to your daemon	Try bumping down your daemon memory to 16g (16g in container and 13g heap) and see Or if you had more than 32g, try 32g container and 28g heap.
2024/03 /03	ALL	ALL	4.11.1	Not important	GRP- 5268	You run Grouper and use the daemon screen	Note that the change log temp daemon and composite change log consumer run continuou If you want to see progress show subjobs (checkbox is default checked in v5)
2024/03 /03	ALL	ALL	4.11.1	Not important	GRP- 5340	You run Grouper and have any rules	Periodically look at your rules, delete invalid ones if they should be deleted.
2024/02 /27	4.10.3	ALL	4.11.0	Medium important	GRP- 5310	You use self signed certs for tomcat	See Jira and adjust env vars
2024/02 /27	ALL	ALL	4.11.0	Medium important	GRP- 5302	lf you use Grouper	If your grouper credential cannot do DDL, see the Jira and run the DDL manually. Otherwise, after the OTHER_JOB_upgradeTasks job runs, the DDL will be added. Look a no issues adding the DDL.
2024/01 /01	ALL	ALL	4.10.2	Medium important	GRP- 5228	If you expect tomcat access logs to be in /tmp (previous default), they are not in /opt /grouper /logs	Set this variable: GROUPER_TOMCAT_LOG_ACCESS_DIRECTORY=/tmp

2023/12 /27	ALL	ALL	4.10.0	Medium important	GRP- 5218	If you set this in grouper. properties	Remové it
						grou per. json seri	
						aliz e. dese rial ize. useL egac	
						y = true	
2023/12 /27	ALL	ALL	4.9.3	Medium important	GRP- 5170	If you patched GSH templates in 4.9.0 or 4.9.1	Remove the patch
2023/12 /27	ALL	ALL	4.10.0	Medium important	GRP- 5195	If you use Grouper	If you have extra indexes on grouper_loader_log, you can remove them. If your DB credential cannot do DDL then add indexes manually from Jira Otherwise, after the OTHER_JOB_upgradeTasks job runs, the DDL will be added. Look a no issues adding the DDL.
2023/11 /26	ALL	ALL	4.7.0	Medium important		If you have a MidPoint provisioner and do not have foreign keys with cascade delete	Either drop the MidPoint tables and use the new DDL, or add cascade delete to the foreign tables
2023/11 /20	ALL	ALL	4.9.0	Medium important	GRP- 5130	If you use the zoom provisioner / loader	A 3rd party library was updated for security, test your integration. Note set this explicitly in grouper-loader.properties, the default will change from true to false.
							<pre># if reactivating users, this will assign a license zoom.myConfigId.licenseReactivatedUsers</pre>
2023/11 /20	ALL	ALL	4.9.0	Medium important	GRP- 5139	If you use the OIDC for UI/WS authenticati on	A 3rd party library was updated for security, test your authentication
2023/11 /20	ALL	ALL	4.9.0	Medium important	GRP- 5140	If you use the legacy (non provisioning framework) box provisioner	A 3rd party library was updated for security, test your provisioner or upgrade to the provisioning framework
2023/11 /20	ALL	ALL	4.9.0	Medium important	GRP- 5141	If you use the legacy (non provisioning framework) google apps provisioner	A 3rd party library was updated for security, test your provisioner or upgrade to the provisioning framework
2023/11 /20	ALL	ALL	4.9.0	Medium important	GRP- 5142	If you use Grouper	JSON marshalling changed to be higher performance and less likely to leak memory. You can use this in grouper.properties to revert to old if you have an issue:
							<pre>grouper.json.serialize.deserialize.useLegacy = true</pre>
							Report any issues you have if you have to revert

2023/11 /20	ALL	ALL	4.9.0	Medium important	GRP- 5082	lf you LDAP loaders of type: list of groups or groups from attributes, and grouper- loader. properties: load er. ldap requ ireT opSt emAs Stem From Conf igGr oup = true or defa ult	You can now specify any stems to be the top stem, or you can use a stem near the loader configured group. After upgrading, run the diagnostics or full sync on your loader and make sure the destination stays the same and does not change. Might want to temporarily remove the SQL like string if applicable so the existing groups do not get deleted.
2023/11 /04	v2.5.0-v2.5.68, v4.0.0-v4.7.2	ALL	4.8.0	Not important	GRP- 5107	If you were affected by the authenticati on bypass vulnerability and installed the remediation	You can safely remove the remediation
2023/10 /04	ALL	ALL	4.7.0	Important	GRP- 4946	If you use provisioning	If you provision based on attribute (e.g. netId or eppn), and the provisioner cannot work if t null, and some subjects dont have that attribute, and you dont want it to raise an error (eve is ignored), then configure the provisioner attribute to not provision the object if the attribute (under validation settings see the jira)
2023/10 /04	ALL	ALL	4.7.0	Important	GRP- 5005	If you want database connection pool size to differ based on UI /WS //daemon (e.g. if you have problems with daemon performanc e or reliability)	You can set the env var in container for DB pool size: GROUPER_DATABASE_CONNEC <sup>•</sup> You can allow the daemon to use more connections than UI/WS. For instance, the daemo twice the pool size as a UI/WS. Do some math based on how maybe connections your DE many nodes of each type you have. For instance, if you have 500 connections max at DB, and 2 daemon, 2 ui, and 2 ws, might daemon to be 110, and ui/ws to be 55.
2023/09 /08	ALL	ALL	4.6.0	Important	GRP- 4932	If you have SSL certs in /etc/pki /java /cacerts (if your SSL if not in trusted roots)	<ol> <li>You can be doing one of three things with SSL certs:</li> <li>Putting them in the container in /etc/pki/java/cacerts         <ul> <li>a. You need to switch to method #2 or #3 (either #2 or #3 is preferred, #2 is best store (not preferred)</li> <li>Putting them in /opt/grouper/certs/client                 <ul></ul></li></ul></li></ol>
2023/07 /25	ALL	ALL	4.5.0	Not important	GRP- 4843	You use GSH templates	If you want a run button from the misc GSH template screen, edit the template and pick th
2023/07 /04	ALL	ALL	4.4.0	Not important	GRP- 4816	You use SQL sync	Multiple source records with same key in SQL sync will cause daemon error (you can confi
2023/06 /27	ALL	ALL	4.4.0, 4.3.0	Important	GRP- 4803	You customize any tomcat config files	The tomcat version changed so make sure any patches or edits or overrides to the tomcat

2023/06 /27	ALL	ALL	4.3.0	Important	GRP- 4805	You use a box external system with a proxy and not default port	
2023/06 /06	ALL	ALL	4.2.0	Important	GRP- 4768	You use Grouper	If your database can support 500 connections for each node in your env, then you do not Otherwise, increase the number of connections your database can support, or change th (used to be 100). Note that file is in the container and cannot be changed dynamically
							hibernate.c3p0.max_size = 500
2023/05 /05	ALL	ALL	4.1.6	Medium important	GRP- 4694	You use Grouper	Upgrade the grouper_memberships_lw_v (manually). Note this is for performance, so the
2023/04 /26	ALL	ALL	4.1.4	Not important	GRP- 4610	If you do not want diagnostics to fail for a day	
2023/03 /26	ALL	4.1.1 or older	4.1.2	Important	GRP- 4679	If you lock down UI configuratio n to ipv6 without a mask, or multiple ipv6 comma separated	•
2023/03 /26	ALL	ALL	4.1.1	Important	GRP- 4657	If you have provisioners	
							the target that is needed a
							Group attribute value cache 0 type groupAttribute groupAttribute groupObject: Store the er attribute if applicable, and translationScript: Transla
							Group attribute value cache 0 group attribute
							Use group attribute value cache 1  LEL?  Default value (False)  If you need to cache some from the target or from gro
							Group attribute value cache 1 source
							Group attribute value cache 1 type Group Attribute groupAttribute groupAttribute groupObject: Store the en attribute # applicable, and translationSerie); Transla
							Group attribute value cache 1 attribute  Group attribute value cache 1 attribute  EL?  DusinessCategory  Pick an attribute from the to store in the database ca
							For entities and groups, you should add a second search/match attribute for the "link" attri
							them out and then select
							Matching attribute(s) same as search attribute(s)           Image: Constraint of the search attribute(s)         Image: Constraint of the search attrinde(s)
							Matching attribute count
							Matching attribute 1 gidNumber The first matching attribut
							Matching attribute 2 L2 [Idap_dn The second matching attribute 2
2023/03 /26	ALL	ALL	4.1.1	Not important	GRP- 4625	If you want auto-ddl configured correctly	**

2023/03 /26	ALL	ALL	4.1.1	Not important	GRP- 4633	If you want the previous default behavior where all users will see some attributes in etc folder	Reconfigure if you want the previous behavior. Recommended not to do this. You should those attributes for power users only
2023/03 /13	ALL	ALL	4.0.3	Important		If you reference cacerts or other trust store files or folders in your Dockerfile or configuratio n (e.g. rabbitmq external system)	If you reference cacerts or other trust store files or folders, the path changed in java17, if you xxx/jre/lib/security/xxx Change it to xxx/lib/security/xxx
2023/03 /13	ALL	4.0.3- only	4.0.1	Important		If you have auto ddl configured in grouper. hibernate. properties	Note, do not change this if upgrading to 4.1.0+ Change auto DDL to 4.*.* (4.0.4+) or 4.9999.9999 (4.0.1)
2023/03 /10	ALL	ALL	4.0.1	Not important	GRP- 4619	If you have a provisioner translation that checks for nulls in a terniary operator, e. g. \${gr oupe rPro visi onin gGro up ? x :y}	Reconfigure to check for nulls per jira
2023/03 /01	ALL	ALL	4.0.1	Important			Check your derived image build and make sure it works with Rocky linux. It is intended to
2023/03 /01	ALL	ALL	4.0.1	Important		You have a subimage or scripts that use the tomee directory	GRP-4567: either make a symlink from /opt/tomcat to /opt/tomee, or change your scripts to Change ENV container vars from TOMEE to TOMCAT
2023/03 /01	ALL	ALL	4.0.1	Important		You have a custom provisioner	The API and capabilities changed slightly, please discuss with Chris on slack
2023/03 /01	ALL	ALL	4.0.1	Not important		You use the legacy SCIM WS (not provisioning !)	This has been rewritten and needs to be adjusted from clients. We are not aware of anyor
2023/04 /28	ALL	ALL	4.0.1	Important		You mount the log directory to the container or use uids and gids somewhere from the container	The tomcat user uid in the container is 996 (was 998), and the group is now 994 (was 997) adjust permissions

2024/01 /19	ALL	ALL	4.0.1	Important	1	You use kerberos for WS authn	Java 17 has stricter encryption types. If authentication is having issues you might either ne credentials to a newer encryption type, or allow old encryption types in the /etc/krb5.conf.
							<pre>allow_weak_crypto = true permitted_enctypes = aes256-cts-hmac-shal-96 aes128- cbc-shal default_tkt_enctypes = aes256-cts-hmac-shal-96 aes12 cbc-shal default_tgs_enctypes = aes256-cts-hmac-shal-96 aes12 cbc-shal</pre>