

cm_co_enrollment_attributes

Table	cm_co_enrollment_attributes
Description	Per-CO enrollment flow attribute configurations

- There is no REST interface to this table since it is intended to configure the COmanage Registry UI.

Column	Format	Description	Definition	Comments
id	integer, primary key	Row identifier	autoincrement	
co_enrollm ent_flow_id	integer, foreign key	CO Enrollment Flow ID	cm_co_enrollment_flows:id	
label	varchar (80)	Name of attribute as presented during enrollment		
description	varchar (256)	Description of attribute, presented during enrollment		
attribute	varchar (80)	CO Person, CO Person Role, or Org Identity attribute name	Attributes defined in cm_co_people , cm_co_person_roles , cm_org_identities or related tables (such as cm_addresses), including cm_co_extended_attributes	
type	varchar(2)	If attribute definition includes a type, associate this enrollment attribute with the specified type		
required	integer	If the flow requires this attribute	1: Required 0: Not required (ie: optional) -1: Not permitted	
required_fi elds	varchar (160)	If this attribute has subfields, a comma separated list of which of those fields are required		Currently applies only to cm_names and cm_addresses . See also cm_co_settings
ordr	integer	Order attribute is presented (lower numbers = earlier)		
hidden	boolean	Whether or not to display this attribute	- true: Do not display this attribute - false: Display this attribute	Only honored when there is a non-modifiable default attribute value
copy_to_c operson	boolean	When the Petition is created, duplicate the value in the attribute from the Org Identity to the corresponding attribute in the CO Person or CO Person Role record		Applies only to Org Identity attributes.
ignore_aut horitative	boolean	Whether or not to ignore authoritative values	- true: Ignore authoritative values for this attribute - false: Allow authoritative values for this attribute	Deprecated, to be removed in Registry v4.0.0
default_env	varchar (80)	If specified, the value held in this environment variable will be used as a default value for this attribute		Added in Registry v3.1.0
login	boolean	For attributes of type Identifier, whether or not to flag the Identifier as able to login to Registry	- true: Identifier can be used to login to Registry - false: Identifier cannot be used to login to Registry	Correlates to cm_identifiers:login
language	varchar (16)	Language encoding of this attributes	RFC 5646	For supported values, see <code>lang.php</code>