

cm_org_identity_sources

Table	cm_org_identity_sources
Description	External sources of organizational identities

Column	Format	Description	Definition	Comments
id	integer, primary key	Row identifier	autoincrement	
co_id	integer, foreign key	If <code>pool_org_identities</code> is <i>false</i> in the CMP Enrollment Configuration , the CO in which this Org Identity Source is available	cm_cos :id	
description	varchar (256)	Description		
sor_label	varchar (40)	SOR Label used in match requests	ID Match API	Added in Registry v4.1.0
plugin	varchar (32)	Org Identity Source Plugin		Corresponds to plugin name
status	varchar(2)	Status of Org Identity Source Plugin	<ul style="list-style-type: none"> A: Active S: Suspended 	
sync_mode	varchar(2)	How to process this Org Identity Source when processed via JobShell	<ul style="list-style-type: none"> F: Full M: Manual Q: Query U: Update 	
sync_query_match_mode	varchar(2)	How to process a Query that returns on an email search but the record does not actually contain that email	<ul style="list-style-type: none"> N: Create a new Org Identity X: Ignore the returned record 	
sync_query_skip_known	boolean	When in Query mode, whether to skip email addresses already linked to records in the Org Identity Source	<ul style="list-style-type: none"> true: Skip known email addresses false: Do not skip 	
sync_on_user_login	boolean	If a CO Person has an Org Identity from this Source, perform a sync when the CO Person logs in to Registry	<ul style="list-style-type: none"> true: Perform sync on user login false: Do not perform sync on user login 	Added in Registry v3.1.0
eppn_identifier_type	varchar (128)	Identifier type in Org Identity Source record to use to create an identifier of type ePPN associated with this Org Identity		
eppn_suffix	varchar (128)	Suffix (right hand side) to append to identifier of type eppn_identifier_type to create an identifier of type ePPN		Should not include @
hash_source_record	boolean	Whether to store a hash of the Org Identity Source Record rather than the full source record		Controls what is stored in cm_org_identity_source_records :source_record Added in Registry v3.1.0
co_pipeline_id	integer, foreign key	CO Pipeline to run when an identity is added from this source	cm_co_pipelines :id	